

SPITFIRE P560



In accordance to:
 EN 15895+A1: 2018
 EN 12549
 Directive Tool:
 2006/42/EC
 Loads:
 2013/29/UE
 EN 16264

Tool specifications	
Name	SPITFIRE P560
Impact force (Joules)	520
Weight (kg)	4.2 (3.7 as single shot version)
Overall dimensions LxH (mm)	363/277/77 (363/215/77 as single shot version)
Ammunition caliber	6.3/16 (10 loads per disc)
Disc loads colors	Yellow, blue, red, black
Pin capacity (nbr)	10 in magazine (1 strip)
Fastener lengths (mm)	26 in strip (single shot also available)

Characteristics
Specialised tool for cladding, roofing & decking
Automatic cartridge advance
No mechanical power adjustment
Quick un-lock system
Easy maintenance
Different nose adapters
Stability STAB system

Safety specifications
CE marking
Indirect action class A1 (A*), velocity < 100 m/s
Complete tool pressure necessary to generate the shot
Window for check disc presence
Noise level at operator, EN 12549: LWA,1s = 118 dB(A) / LpA,1s,0 = 111 dB(A) / Lp Cpeak = 144 dB(C)
Vibration: < 2.5 m.s ⁻²

Accessories	Consumables
Magazine	HSBR14 strip
Single shot pin guide	HSBR14
Kit SA12-8	SA12-8 + RE 25 to 40